


# PosiTector® 200 Series



Coating Thickness  
Gages for measuring  
on Concrete, Wood,  
Plastic and more...



Advanced  
models  
measure up  
to 3 layers  
with graphics



Available on the  
App Store



**DeFelsko®**  
The Measure of Quality

# PosiTector® 200 Series

## All Gages Feature...

### Simple

- Ready to measure—no adjustment required to measure most coatings
- RESET feature instantly restores factory settings

### Durable

- Solvent, acid, oil, water and dust resistant—weatherproof
- Shock-absorbing, protective rubber holster with belt clip
- Two year warranty on body AND probe

### Accurate

- Responsive transducers provide fast, accurate readings
- Certificate of Calibration showing traceability to NIST or PTB included
- Proven non-destructive technique conforms to ASTM D6132 and ISO 2808

### Versatile

- PosiTector body accepts all PosiTector probes easily converting from a coating thickness gage to a surface profile gage, dew point meter or wall thickness gage
- Flip display enables right-side-up viewing
- Uses alkaline or rechargeable batteries (built-in charger)

### Powerful

- Continually displays average, standard deviation and min/max thickness
- USB port for connection to a Mac/PC and to supply continuous power
- Every stored measurement is date and time stamped
- PosiSoft USB Drive—stored readings, graphs and screen captures can be accessed using universal PC/Mac web browsers or file explorers. No software required.
- Includes PosiSoft Suite of solutions for analyzing and reporting data



Select from a variety of measurement ranges			
Probes	200B	200C	200D
Typical Applications	Polymer coatings on wood, plastic, etc.	Coatings on concrete, fiberglass, etc.	Thick, soft coatings such as polyurea, asphaltic neoprene, very thick polymers, etc.
Measurement Range*	13 – 1000 µm 0.5 – 40 mils	50 – 3800 µm 2 – 150 mils	50 – 7600 µm 2 – 300 mils
Accuracy	+/- (2 µm + 3% of reading) +/- (0.1 mil + 3% of reading)		+/- (20 µm + 3% of reading) +/- (1 mil + 3% of reading)
Minimum Layer Thickness^	13 µm 0.5 mil	50 µm 2 mils	500 µm 20 mils

\* Range limits apply to polymer coatings. D probe— polyurea range is 50–5000 µm (2–200 mils).  
^For multiple-layer applications only. Dependent on material being tested.

## Select Standard or Advanced Features

### Standard Models

Includes ALL features as shown on left plus...

- Measure the total thickness of a coating system
- Backlit monochrome display with transfective technology
- Storage of 250 readings


### Advanced Models

Includes ALL features as shown on left plus...

- Measure the total thickness of a coating system or up to 3 individual layer thicknesses in a multi-layer system. Also features graphic readout for detailed analysis of the coating system
- High Contrast reversible color LCD
- Storage of 100,000 readings in up to 1,000 batches
- Graphics mode with screen capture
- Real-time graphing, picture prompting and batch notes
- Onscreen Batch Annotation—add notes, change batch names and more with built-in QWERTY keyboard
- WiFi technology wirelessly communicates with PosiSoft, downloads software updates and connects with mobile devices for expanded functionality
- Bluetooth® Wireless Technology for data transfer to a computer or optional portable printer

For a complete comparison of the Standard and Advanced features visit [www.defelsko.com/p200](http://www.defelsko.com/p200)

Easy-to-read graphic display provides clear, detailed analysis of coatings.



Advanced Model shown in Graphics mode

All gages come complete with body and probe, ultrasonic gel, precision plastic shims, protective rubber holster with belt clip, wrist strap, 3 AAA batteries, instructions, nylon carrying case with shoulder strap, protective lens shield, long form Certificate of Calibration traceable to NIST or PTB, USB cable, PosiSoft.net account, two year warranty on body and probe.

**Size:** 135 x 61 x 28 mm (5.25" x 2.4" x 1.1")

**Weight:** 140 g (4.9 oz.) without batteries  
Conforms to ASTM D6132 and ISO 2808



# PosiSoft® Suite of Software

3 FREE ways to view and report your data

## PosiSoft Desktop Software (v 4)


Powerful desktop software (PC/Mac) for downloading, viewing, printing and storing measurement data. Includes customizable, templated PDF Report Generator. No internet connection required.

- Import readings directly from the gage via USB
- **Jobs** feature consolidates and organizes batches and reports
- Export all data, settings and templates for backup and sharing



## Generate Custom, Professional PDF Reports

- Include inspection information such as on-site pictures, screen captures, notes and more to communicate important details
- Create and save multiple custom layouts as templates – insert cover pages, add logos/images, and select font and point size
- Select the information to include for each product type – charts, histograms, readings, time stamps and more
- Compile multi-batch reports from one or more instrument types



## PosiSoft.net

A web-based application offering secure centralized management of readings. Access your data from any web-connected device.


- Synchronize measurement data when connected via USB, Bluetooth or WiFi wireless technology
- Securely store measurement data in the cloud and share with authorized users via a secure login
- Generate reports with graphs, annotations and images



## PosiSoft USB Drive

A simple interface to retrieve data from your gage in a manner similar to a USB flash drive. No software required.

- Measurement data can be printed quickly from an HTML report or exported in .CSV format for further analysis in Excel



Learn more at [www.DeFelsko.com/PosiSoft](http://www.DeFelsko.com/PosiSoft)

	PosiSoft Desktop	PosiSoft.net	PosiSoft USB Drive
Generate basic, pre-formatted reports	◆	◆	◆
Generate professional PDF reports with custom formatting. Add pictures, logos, screen captures, notes and more.	◆	◆	
Export to .CSV (comma separated values)	◆	◆	◆
View and print readings stored on a PosiTector/PosiTest AT-A	◆	◆	◆
Add photos and notes to reading data	◆	◆	
Software installation required	◆		
Internet connection required		◆	
Default download location for batches and readings	<b>Hard Drive</b>	<b>Cloud</b>	<b>Gage</b>
Multi-language support: English, Spanish, German, French, Chinese and Korean	◆	◆	◆*
PC/Mac compatible	◆	◆	◆
FREE	◆	◆	◆
Compatible with all current <b>PosiTector 6000/200/SPG/RTR/DPM/UTG</b> and <b>PosiTest AT series</b>	◆	◆	◆†

\*PosiSoft USB Drive supports all 15 languages supported by the PosiTector gage. † PosiTest AT-M is not supported by PosiTector USB Drive


  
**研士強國際集團 YENSTRON GROUP**
  
**益瀚國際科技股份有限公司**
  
 台中總公司: 407227台中市西屯區工業區一路2巷7號1F
   
 TEL: (04)2359-3199 FAX: (04)2359-8507
   
<http://www.yenstron.com.tw>