

NEW



Professional Shore hardness tester

Features

- **Shore A, 0 and D** to measure the hardness of plastics through penetration measurement
- **Shore A** rubber, elastomers, neoprene, silicone, vinyl, soft plastics, felt, leather and similar material
- **Shore 0** foam, sponge
- **Shore D** plastics, formica, epoxides, plexiglass etc.
- **Internal memory** for up to 500 measurements
- Delivered in a hard carrying case
- Particularly recommended for internal comparison measurement. Standard calibrations e. g. to DIN 53505 are often not possible because of very narrow standard tolerances
- Can be attached to the test stands TI-A0L (for Shore A and A0), TI-DL (for Shore D) to improve measuring uncertainty
- Large display with backlight
- Selectable: AUTO-OFF function or continuous operation, charge indicator


Technical data

- Tolerance: 1 % of [Max]
- Overall dimensions WxDxH mm
- Net weight approx. 173 g
- Permissible ambient temperature 0 °C / 50 °C
- Transfer via RS-232 to the PC, e.g. to Microsoft Excel
- Measuring frequency: 30 display updates per minute

Accessories

- **Software** interface cable included, SAUTER ATC-01
- **1 7 hardness comparison plates** for Shore A, tolerance up to ± 2 H, SAUTER AHBA-01
- **2 3 hardness comparison plates** for Shore D, tolerance up to ± 2 HD, SAUTER AHBD-01
- **Optional ISO calibration of the comparison plates**, SAUTER 961-170
- **Test stand** for HDA and HDO, SAUTER TI-A0L
- **Test stand** for HDD, SAUTER TI-DL

STANDARD



OPTION



YENSTRON®
 研士強國際集團 YENSTRON GROUP
 益瀚國際企業股份有限公司
 台中總公司: 40767台中市西屯區工業區一路2巷7號1F
 TEL:(04)2359-3199 FAX:(04)2359-8507
<http://www.yenstron.com.tw>

Model	Hardness type	Measuring range	Readout
SAUTER		[Max]	[d]
HDA 100-1.	Shore A	100 HA	0,1 HA
HDO 100-1.	Shore A0	100 H0	0,1 H0
HDD 100-1.	Shore D	100 HD	0,1 HD