

DUAL INPUT K-type THERMOMETER



Made in TAIWAN Brand : *tstr* Model : TS-1321

Introduction

- ◆ Big LCD, T1 and T2 Dual Display (LCD 18.2mm), High Resolution, Quick Reaction
- ◆ Resolution : 0.1°C / 0.1°F (below 1000°C)
- ◆ Function : °C/°F, MAX/MIN, HOLD, REL, MEM, LIMIT, HI/LO, TYPE, T1-T2, PC, MEM--to save 10 data
- ◆ it could save 10 data; it's able to call/delete the data anytime
- ◆ Auto Power OFF could remove manually, Low battery indication
- ◆ Increase USB or RS232 interface, and adopt all optic coupling to be transmitted
- ◆ Support VISTA , XP , ME , 2000 operating systems , PC software is simple and easy to operate, convertible English, Traditional Chinese, simplified Chinese character show at present
- ◆ CE-Mark approval, Conform to ITS-90

Specification

1. Dual Display (LCD 18.2mm)
2. K-type : -200°C ~ 1372°C (-328°F ~ 2501°F)
3. Resolution : 0.1°C / 0.1°F (below 1000°C)
4. Operation Temperature and Humidity : 0°C ~ 50°C ; 80%RH
5. Storage Temperature and Humidity : -10°C ~ 60°C ; 80%RH
6. Power requirement : R03(AB) / SIZE AAA / 1.5V / UM-4 X 4PCS
7. Input protection at thermocouple input : AC/DC 24Vrms.
8. Dimension (including cover) :
125 mm (L) X 82 mm (W) X 43 mm (T)
9. Weight (including cover) : Approx 350 g
10. MEM--to save 10 data, Auto Power OFF, Low battery indication
11. Accessory : K-type thermo probe (approx 90 cm), 2 pcs



Research and design manufacturing~

YENSTRON CORP.

Address : No.7, Lane 2, 1ST. Road, Taichung

Industrial Park, Xitun Dist., Taichung 40767, TAIWAN

TEL: +886-4-23593199 FAX: +886-4-23598507

Int'l Sales Depts. E-mail: yenstron@hibox.hinet.net

Website : <http://www.yenstron.com.tw>

TEL : +886-4-23593199

solutions for testing